ELEVATION
DETAIL III - LIFTING EYE

DETAIL IV

DETAIL IV
STAINLESS STEEL FERRULES

RETAINING STRIPS FOR RUBBER SEALS
( for one pair of doors)

NOTES
1)ALL FULL WELDED CONSTRUCTION FOR MILD STEEL.
2) DOORS MUST BE PLANE ALONG BOTH SKIN PLATES AND ALL FRAME CORNERS TRUE 90°
3) STEEL SURFACE FINISH TREATMENT:
GRIT BLASTING
PAINT SPRAYING OF ONE COAT TRANSPOXY PRIMER 1.16
AFTER DRY, ONE COAT OF TRANSPOXY HB INTERMEDIATE 2.19 UNDERCOAT
AFTER DRY, TWO COATS OF TRANSPOXY TAR AA 2.2
MIXING OF PAINTS IS PROHIBITED.
5) AN ALTERNATIVE TO THE ABOVE TREATMENTS WILL ONLY BE ACCEPTED AFTER WRITTEN PERMISSION IS OBTAINED FROM THE ENGINEER
6) ONE DOOR IS ONLY SHOWN - BOTH DOORS SYMMETRICAL
7) WHERE 200X75X20 STEEL PLATE TOUCH TO THE CONCRETE WALL. GIVE RUBBER STOP TO CONCRETE
8) 7 ∅9 HOLES 225C/C
NUMBER OF HOLES DIAMETRE OF HOLE DISTANCE BETWEEN CENTRE
9) IN THE CORNERS FIRST FERRULES ON A DISTANCE OF 100mm FROM THE EDGE OF THE DOOR
NB ALL FERRULES BOLTS AND WASHERS SHALL BE SUPPLIED
10) CONTRACTOR MUST ASCERTAIN ALL DIMENSIONS AND LOCATION OF THE STRUCTURE BEFORE ANY CONSTRUCTION

REFERENCE
N/D/LB 1173 DOUBLE BARREL TIDE GATE STRUCTURE
N/D/LB 1171 STEEL DOOR LOWER BEARING
N/D/LB 1172 STEEL DOOR UPPER BEARING

| VARIATIONS | NAMES | DATE |
|---|---|---|
| | | |

| | |
|---|---|
| DRAWN<br>V.ALIFERETI | DATE<br>OCTOBER 2020 |
| DESIGNED<br>KHIN MAUNG CHO | CHECKED |
| SENIOR DRAFTSPERSON | |
| SENIOR DESIGN ENGINEER | |
| PRINCIPAL ENGINEER<br>KHIN MAUNG CHO | |
| SCALE<br>1:10 | |

MINISTRY OF WATERWAYS & ENVIRONMENT
DEPARTMENT OF WATERWAYS
LEVEL 3 BALI TOWER
318 TOORAK ROAD
PO BOX 1292
SUVA

PROJECT
SOASOA DRAINAGE SCHEME

DRAWING TITLE
2. DETAILS OF STANDARD STEEL DOOR FOR CAST IN SITU OUTFALL STRUCTURE

| | |
|---|---|
| SHEET 3<br>OF 3 SHEETS | DRAWING NUMBER<br>N/D/LB 1170 |